

	Industrial														
Unit	<i>FumeFighter</i>	<i>F62B</i>	<i>F33/V</i>	<i>F66/V</i>	<i>F73</i>	<i>M32/V</i>	<i>M33/V</i>	<i>M66/V</i>	<i>M73</i>	<i>M67</i>	<i>M68/V</i>	<i>Porta Air</i>	<i>AQE 2000</i>	<i>AQE 4000</i>	
Uses	Soldering, VoC's, Light Welding, Brazing	Welding smoke, mist collection, general smoke, oil/grease	Welding Smoke, Mist Collection, Wet Grinding, Misc. Smoke			Welding, Grinding, Hex Chrome Filtration, VOC Capture, Purging/Plastics				Grinding, Smoke, Light VOC	HEPA Required Applications		Dust Collection, Welding, Grinding		
Capture Method	Source	Ambient	Ambient and Source						Ambient	Ambient/Source	Source		Ambient and Source		
Filtration Technology	HEPA and Carbon	Electrostatic				Media and optional Carbon				Media	Media (HEPA)	Cartridge Media			
Airflow	225cfm	2500cfm	1250cfm	2600cfm	6000cfm	1250cfm		2500cfm	5500cfm	1980cfm	2000cfm	1000cfm	1100cfm	2500cfm	
Dimensions	22.5"L x 17"W x 27"H	29.5"L x 27"W x 31"H	41"L x 14.5"W x 26.5"H	41"L x 27.5"W x 26.5"H	53.62"L x 46.44"W x 29.20"H	44"L x 14.25"W x 27"H	40"L x 20"W x 73"H	27.2"H x 26.5"W x 56"L	46.5"L x 49.5"W x 29.2"H	24"H x 24"W x 47"L	27.1"H x 26.5"W x 46"L or 48"L	46"H x 27"W x 37"D	46"H x 28.5"W x 37"D	21"H x 58"W x 98"D	
Color	Baked enamel Ivory				Galvanized	Baked Enamel, Ivory			Galvanized	Baked Enamel, Black	Baked Enamel Ivory				
Construction Material	18 ga welded steel	16 ga welded steel													
Weight (Installed)	70 lbs	225lbs	195 lbs	280 lbs	495lbs	185lbs	200 lbs	250 lbs	405 lbs	120lbs	296 lbs	350lbs	400 lbs	656 lbs	
Mount	Portable	Ceiling	Wall, Ceiling, or Portable		Wall or Ceiling Mount	Wall, Ceiling, or Portable			Wall or Ceiling Mount		Wall, Ceiling, or Portable	Portable		Ceiling, Wall, or Floor Stand	
Key Feature	Variable speed motor, carbon, large filter area (high capacity), and HEPA filter included.	Coanda Airflow pattern, no consumables (esp based), minimal amp draw, wide range of uses (versatile).	Washable electrostatic filters (No replacement filters needed).			Variety of filter and accessory options.				Cost effective, 3-speed, easy access to front loading filters, available 2" Carbon Filter, Used in Commercial and Light Industrial Applications.		HEPA filter standard, variety of accessory options.	Cheaper version of the AQE 2000 minus the reverse pulse system.	Portable, Source Capture, Reverse Pulse Cleaning, 360 degree arm rotation.	Reverse Pulse Cleaning, Options: Spark Arrestors, Explosion Relief Panels, Photohelic Controller, wide selection of filter options.

FOOTNOTE 1: "/V" DENOTES PORTABLE UNITS THAT HAVE SOURCE CAPTURE ARM CAPABILITY.

FOOTNOTE 2: ALL INDUSTRIAL UNITS COME WITH CONTROL CIRCUITRY INCLUDED.